

COMMERCIAL WASHER



easywash®

OHS 13
OHS 16
OHS 22
OHS 27

- ▶ Stainless steel construction - bucket, drum, top, front and side panels - for better appearance and quality.
- ▶ Equipped with heavy-duty frame and bearings, durable bearing housing and shaft - to greatly reduce wear and tear.
- ▶ Automatic mixing of water at a precise temperature with the programmed water level - to save energy and reduce wash cycle time.
- ▶ Advanced inverter drive system and special heavy-duty motor - guarantee smooth operation and reliable performance.
- ▶ Better balance control system to ensure smooth operation, reducing washing time and saving energy.
- ▶ Front detergent compartment with dosing system connection - for easier access and use.
- ▶ High spin speed up to 330G - removes more water to reduce drying time and save energy - no need to screw into the ground.
- ▶ Double safety door lock system - ensures safe operation and minimizes the risk of accidents.
- ▶ Full control with touch screen and UV light.

COMMERCIAL WASHER



HS13 HS16 HS22 HS27

DRUM					
Diameter	mm	650	650	750	750
Depth	mm	340	420	455	560
Volume	L	115	145	200	250
Loading capacity	kg	13	16	22	27
SPEED					
Washing speed	rpm	32	32	32	32
Mediate speed	rpm	420	420	420	420
High extracting	rpm	910	910	850	850
G-force		300	300	300	300
DOOR					
Height center to floor	mm	707	707	821	806
Height bottom to floor	mm	427	427	542	527
Diameter	mm	410	410	410	410
POWER					
Motor	kw	1.85	2.2	3	3.7
Heating for electric model	kw	12	12	16	20
CONNECTIONS					
Water inlet	inch	3/4	3/4	3/4	3/4
Drain diameter	inch	3	3	3	3
Drain (floor to center)	mm	85	85	115	115
DIMENSIONS					
Width	mm	840	840	939	939
Depth	mm	820	900	987	1087
Height	mm	1307	1307	1447	1447
Net weight	kg	250	260	360	410

easywash Private Company

7A, PENTELIS AV. - VRILISSIA - 15235

Phone: 2106849600 & 2106849604

email: info@easywash.gr - www.easywash.gr